AZ-420B SPECIFICATIONS

**World Leader in Portable Reclaimers / Stabilisers / Utility Trenchers** 



The AZ-420B harnesses the power and productivity of much larger self-propelled stabiliser / reclaimers into a very powerful, versatile and affordable loader attachment. Powered by a Cummins (Tier 3) intercooled turbo-diesel engine, the AZ-420B will pulverize up to 250mm in a single pass with productivity up to 450m2 / hr. Heavy patches, full road repairs, base stabilisation, gravel roads and opening utility trenches in asphalt are just a few of its many uses.

## **CONTACT US FOR DEMONSTRATION AND HIRE DETAILS**

02 43851041

**Roadbase Stabiliser** 

## **Features**



Magnum-duty, case-hardened planetary ensures maximum durability and reliability.



**Hydraulic depth adjustment** provides convenient, accurate control of cutting depth.



**Pressurized belt tensioning** conveniently provides consistent belt tension and improved shock handling.



**Boom-mount water supply system** is available in 150-gallon size.

## **Controls and Monitoring**



Host vehicle control box provides loader operator with a comprehensive engine monitoring computer, tachometer and hardwired emergency stop (E-Stop).



Wireless remote control gives maximum control, convenience, and safety in operating the Asphalt Zipper®. Regulates engine speed, depth adjustment, and machine stop.

## **Specifications**

Turbo-Diesel Engine Options	Cummins 110 hp	Planetary	Magnum-duty Fairfield planetary
Torque	306 ft·lb 415 N*m	Transport	Tows behind ¾-ton pickup on single-axle trailer (included)
Cutting Speed	4600 ft²/hr 450m²/hr	Mounting	Mounts on most backhoe buckets
Weight	5800 lbs 2631 kg	Cutting Teeth	Bullet-head, carbide-tipped
Cutting Width	42 in (18" to 42" available) 762 mm (914, 609 or 457 mm available)	Depth Control	Hydraulic
Cutting Depth	0 to 10 in 0 to 254 mm	Additional Features	<ul><li>Top-opening bit hatch</li><li>Pressurized belt tensioning</li><li>Hydraulic bucket clamps</li></ul>

